IN GOES THE BAD AIR...

OUT COMES GOOD AIR.



HEPA-FLOWTM WALL MOUNT APS

When it comes to airborne pathogens, normal protective measures - like surgical masks - offer little protection and ordinary air filtration devices can actually contribute to the problem by becoming breeding grounds.

THE HEPA-FLOW™ WALL MOUNT AIR PURIFICATION SYSTEM (APS)

A COMPLETE SYSTEM OF DEFENSE

Increase PATIENT SAFETY and protect yourself and your staff against airborne pathogens with the HEPA-FLOWTM Wall Mount APS.

SUPERIOR PERFORMANCE

The **HEPA-FLOW**TM **Wall Mount APS** has a fully adjustable speed control that can filter up to 575 cubic feet of air per minute, providing a complete exchange and purification of all the air in a typical room 25+ times every hour.

FILTRATION

Unlike other air purifiers, the **HEPA-FLOWTM Wall Mount APS** uses a curved filter design that allows UVC germicidal radiation to bathe the entire filtering surface - maximizing the kill effect and eliminating shadows where pathogens can hide.

HOSPITAL-GRADE HOUSING

The HEPA-FLOWTM Wall Mount APS is enclosed in an attractive, durable and easy-to-clean shell that will not dent, scratch or rust. The unit is designed to minimize noise, make efficient use of wall space and reduce risks of injury with rounded edges and corners.

TAMPER-PROOF CONTROLS

Key-secured operation ensures that only authorized staff can set and change critical CFM/negative pressure settings.

FEATURES

EXCEEDS CDC GUIDELINES
CLINICALLY ENGINEERED AND DESIGNED
ECRI & CRA PERFORMANCE TESTED
TOLL-FREE CUSTOMER SUPPORT
COMPREHENSIVE USE & CARE GUIDE
NO-TOOL STANDARD MAINTENANCE
BLENDS WITH EXISTING DECOR
FDA REGISTERED, CLASS II MEDICAL DEVICE
MANUFACTURED UNDER ISO-9001 STANDARDS

www.airpuretech.com



HEPA-FLOWIM

PORTABLE APS



GENERAL SPECIFICATIONS

FEATURE PERFORMANCE

Pressurization Capability Air Changes

Audible Noise Airflow Direction

DESCRIPTION

Negative, Partial or Full Exhaust 25+ times per hour in 10' x 15' x 9' ceiling room ≤56dBA @ 3 feet from inlet port Floor to Ceiling

CONTROL PANEL

Power Switch Run Timer Power Indicator Magnehelic Gauge Mini-Breaker Key Operated Maintenance Meter Operating Status Filter Monitor External Power Reset

ELECTRICAL

Voltage: 115 Vrms @ 60 Hz Line Cord Supplied UL Approved Current: 8.3 Amps

CABINET

Material Locked Access Cover Plug High-Impact Hospital-Grade Plastic 4 Corners Polarized AC

FAN

Airflow Speeds Power Consumption Speed Adjustment Lubrication Up to 575 CFM (Cubic Feet/Minute) High, Low (Fully Adjustable) 1000 Watts Variable Permanent

FILTERS

HEPA Filter Pre-Filter

99.99% Efficient @ 0.3 Microns 30% ASHRAE

UV LIGHT

5 Watts Location Continuous Illumination @ 253.7nm Capture Side of HEPA Filter

INSTALLATION

Floor Wall Yes- With Locking Casters Yes

RECOMMENDED MAINTENANCE

30% ASHRAE Pre-Filter Change HEPA Filter Change UV Light Change Monthly Annually/8000 Hours Annually/8000 Hours

OPTIONS

Motion Detector to Automatically Control Fan Speed Negative Pressure Hood Pressure Monitoring System Wall Mounting Brackets

DIMENSIONS

Height: 53" Weight: 151 lbs. Depth: 14" Width: 26 1/4" Shipping Weight: 194 lbs.

www.airpuretech.com



AIR-PURE SYSTEMS

Helping You Breathe Kinder-Aire

www.cleanairfacility.com